

Flat End Grab Bar

Item Code and Description

a. 01210-WH ... 18" flat end grab bar, white

General Product Description

- a. a tubular steel grab bar with flattened ends for mounting plates
- b. mount to a wall backed with solid wood blocking, or to concrete, concrete block, or brick

Physical Characteristics

- a. made of tubular stainless steel
- b. polyester epoxy powder coated
- c. grip diameter: 1"
 d. distance from grab bar to wall: 13/4"
- e. overall length: 221/8"
- f. color: white
- g. two mounting holes at each end
- h. 418 lb. load rating when properly installed
- i. fasteners not included due to the vast variety of wall and blocking types and thicknesses

Performance Characteristics

- a. narow profile
- b. no-rust construction
- c. may be installed outdoors and in wet locations like showers
- d. easy to clean (use mild detergent; do not use abrasive pads, or strong acidic, alkaline or other harsh cleaning materials as this may cause discoloration). After cleaning, always flush with water.
- e. grab bars must be mounted to substantial, well-secured blocking usually of 2× solid wood (toenailing is not sufficient; use cleats or notch blocking into studs), though brick, concrete, or concrete block can also be suitable mounting materials
- f. #10 round head fasteners or hex head fasteners recommended (do not use flat head type fasteners; use stainless steel fasteners in wet area installations; each fastener must be capable of withstanding 77 lbs. of pull-out force; the length of fasteners will depend on the distance to drive them deeply into an appropriately reinforced surface capable of supporting the load; drive a properly sized fastener into every mounting plate hole to achieve the full load rating

Compliance

a. conforms to 96 hour salt spray test (ASTM B117-87)

Other Information

- a. 5-year limited warranty when installed in commercial settings
- b. 10-year limited warranty when installed in residential settings
- c. see AKW warranty for details



Flat End Grab Bar





